The Most Dependable

Source For Your

Electrical Needs























GANDHI INDUSTRIAL ELECTRICALS

Introduction



Power which brings development to the nation and joy to the human life, We deliver power solution and products for success of our customers.

Innovative and friendly services offer to our customer have made us one of the leading electrical distributors in the city.

Over the years we have added wide range of products in our premise.

Our Vision:

To focus and ensure customers satisfaction by full filing their needs and expectation with supply of quality products & friendly services all the time.

Our Mission:

To create a unique operational excellence, path breaking customer service and compelling marketing, to bring more advance and innovative products in our premise to benefit our customers & society

Channel Partner / Stockist / Dealer





AUTHORISED DISTRIBUTORS



MPCB



MCCB



Contactors



Isolators



Complete Solution



ACB



EFR



Panel Meter



Overload Relays



Weather Proof Plug & Socket



Distribution Board






RCCB



Energy Meters



Starters

GANDHI INDUSTRIAL ELECTRICALS





THE WIDEST
RANGE BACKED
BY THE FINEST
SERVICE.
WE GO THE EXTRA MILE.




GANDHI INDUSTRIAL ELECTRICALS

SIEMENS



Low Voltage Controls & Power Distribution Products























GANDHI INDUSTRIAL ELECTRICALS



AUTHORISED DISTRIBUTORS



ACB



MCCB




SFU'S



Power Contactors



MCB



MPCB



Mini Contactors



EMPR



Capacitor Duty Contactor



Overload Relays



Fuse



Push Button Station



Panels



Starters



Distribution Board



GANDHI INDUSTRIAL ELECTRICALS

CSPC Protection Relays



AUTHORISED DISTRIBUTORS



NUMERICAL FEEDER PROTECTION RELAY



NUMERICAL MOTOR PROTECTION RELAY



NUMERICAL IDMTL 30/C + 1E/F

RELAY



AUTOMATIC POWER FACTOR CONTROL RELAY (APFCR) 6 STAGE / 8 STAGE / 12 STAGE



ELECTRONIC MOTOR PROTECTION RELAY 6 A / 60 A



AMF CONTROLLER



NUMERICAL REVERSE POWER RELAY



NUMERICAL UNDER & OVER VOLTAGE RELAY



DIGITAL METERS

GANDHI INDUSTRIAL ELECTRICALS



AUTHORISED DISTRIBUTORS



Contactor



Overload Relays



Changeover



MCCB





Isolators



ACB



CAM Lock Fuse Holder





Main Switch



Distribution Board



Wires & Cables



RCCB



MCB



Distribution Board



Modular Switches



MANAGE STATE OF THE STATE OF TH **Domestic Lightings**

Flood Lights

Industrial Lightings

GANDHI INDUSTRIAL ELECTRICALS



TIBREWALA ELECTRONICS LIMITED

An ISO 9001-2008 Company

Introduction

As one of the most renowned manufacturers of Capacitors and MPP Film in India, **Tibrewala Electronics Limited (TEL)** has successfully reached the elite 100 Crore segment, having ventured to capture global markets across Asia, Africa, Australia, Europe and America. With an established presence of nearly three decades in the sector we have become an invaluable resource in the manufacture of industrial machinery and domestic appliances of several reputed international brands and even defence electronics, and presently over 40% of our products are earmarked exclusively for export. With a staggering investment of over 64 crores, today we proudly stand on the threshold of phenomenal outbound growth, adding value to our partners, customers and vendors, stronglycontributing to the nation's industrial strength.

Quality Systems

Tib conproducts conform to global industry norms and international standards such as:

ISO 9001-2008

UL810 (Underwriters Laboratories)

CSA (Canadian Standards)

CE(European-Declaration of Conformity)

ISI (Indian Standards Institution)







Products

- AC Capacitors
- LT Capacitors

AUTHORISED DISTRIBUTORS

GANDHI INDUSTRIAL ELECTRICALS







NEPTUNE

Connecting
Distributing
Managing
Control
Saving
Quality

AUTHORISED DISTRIBUTORS

GANDHI INDUSTRIAL ELECTRICALS













BCH ELECTRIC LIMITED

















GANDHI INDUSTRIAL ELECTRICALS





TEKNIC / RAAS CONTROL / ESBEE / SCHNEIDER 22.5mm / 16mm PUSH BUTTON SWITCHES

Flush Type / Booted Type, Mushroom Button / Mushroom Stayput, Selector (2/3 Position) Maintained, Selector (2/3 Position) Spring Return, Key Selector (2/3 Position, Mushroom With Key, Jumbo Mushroom, Joystick Controller (2/4) Position Mainted & Spring Return.



INSTRUMENT COOLING FANS - REXNORD / JAINSON

Instrument Cooling Fans 12v To 440v A/C, D/C Square & Round Model Size: 3" 4" 6" 8" 10"




MEASURING INSTRUMENTS (DIGITAL & ANALOG)

Clamp Meter (A/C D/C), Multi Meter, Tacho Meter, (contact Type, Non Contact Type) Temperature Controller Size: 48x48, 72x72, 96x96, Meggers, Earth Tester, Thermometer



OEN / OMRON / SALZER - PLA RELAY"S


Electro Magnetic Plugin Relay 6/12/24/48 110/220v - A/C D/C 8 Pin And 11 Pin, On Relay, Off Relay, Rapid Stop, With Led, Without Led.



WAGO / CONNECTWELL / ELMAX / JAINSON - CLIP ON TYPE TERMINALS

Clip on Type Terminals, Standard Terminal Blocks, Stud Type Terminal, Bus Bar Terminals, Disconnection & Testing Terminal Unbreakable Terminal, Polymide Terminal in all Colour.





CABLE MANAGEMENT SYSTEM

G.I. Tray Frp Cable Trays, Perforated Cable Trays, Ladder Cable Trays & Accessories.



CRIMPING TOOLS - JAINSON / DOWELLS / ASHWIN

For Copper / Aluminium Terminals & Connectors .05 sq.mm - 1000 sq. mm Hand & Hydrolic Operated



KSS / GIANT LOCK WIRING ACCESSORIES

Cable Ties, White, Black 75mm, 100mm, 150mm, 200mm, 250mm, 300mm, 368mm, 450mm, 500mm, 750mm, 1020mm Tie Mount 19mm, 25mm



PROXMITY SENSOR, SSR, PHOTO SENSOR

Proximity Sensor Metallic and Non Metallic in Various Size and Sensing Distances in A/C and D/C Versions, SSR Single and Three Phase in all Model Viz D/C to A/C, A/C to A/C, D/C to D/C in 16, 25, 40, 63 amps Photo Sensor in Two Basic Model Viz, Diffuse Scan and Through Beam Type.



SIEMENS / SCHNEIDER / C&S / HAVELLS / L&T - MCB, ELECB, MCCB

MCB Single Pole, Double Pole, Three Pole, Four Pole, in Various amps, MCCB in Different Breaking Capacity





ROTARY SWITCHES

Ammeter, Voltmeter, Phase Selector, Forward Reverse Changeover, Program Switch, Rotary Switches Type All Range 6 amps To I 00 amps Available



HRC FUSE HOLDERS, BASE & FUSE LINK

HRC Fuce Holders 20 amps To 125 amps, HRC DMC Fuse Base 100 amps To 630 amps, HRC Fuse Link NS Type TIA Type, HF Type, HN Type & all Types



PVC / METAL WATER TIGHT ENCLOSURE

Various Size & Models Up To IP65 Protection are Available Ex-Stock



INDUSTRIAL SIREN, PENAL BUZZER & HOOTER

From Various Range 100mts - 5 km Multi Voltage Like' 12V/24V/110V/230V/440V.



SWITCH FUSE UNIT & CHANGE OVER

SFU / CO are Available From 32amps. - 1200 amps. In 3 & 4 Pole Range With & Without Enclosures In Various Brands Like: L&T / Siemens / Havells / Standard / C&S.





HEAVY DUTY MULTI POLE INDUSTRIAL CONNECTORS

Multi Pole Industrial Connectors (Plug & Socket)
Bottom Open & Close up to 48 Pins are Available Ex-Stock



CABLES & WIRES

0.5sq.mm - I 20sq.mm In Multi Single Core & XLPE UG Cables From 2.5sqmm - 630sqmm In Both Aluminium And Copper Upto I Ikv are Available With Exise Gate Pass



CABLE GLANDS & LUGS

Nickle Coated In Single And Double Compressor Available Upto 630sqmm In Brands Like : **COMMET/ JAINSON** / **GIE**



MOTOR STARTERS & CONTACTORS / OVER LOAD RELAYS

Brands Like: L&T / BCH / TC From 6 amps - 800 amps With 3P & 4P Options & Up To 50HP Available Ex-Stock



LUMINARIES: PHILIPS/HAVELLS/BAJAJ

Industrial Flood Light & Indoor Lighting From 1 I watts - 1000 Watts are Available In Various Range Upto Protection IP 65





CURRENT TRANSFORMERS & COILS

30/5a - 3000/5a 5va / I5va Clamp Type TNEB Type With R/Y/B/B Colour Coding Available In Various Size as Per Requirements



AIR CIRCUIT BREAKERS & AUTOMATIC TRANSFER SWITCH

Available In 600amps - 4000amps In 3P / 4P, Manual & Micro Process Based

Brands Like: SCHNEIDER / L&T / C&S / HAVELLS /SOCOMEC



LIMIT & MICRO SWITCH

Available In Wide Range Like: Normal Action, Snap Action, Adjustable Lever Up To 100amps.



KWH METERS / APFC RELAY MICRO CONTROLER / TOTALIZER



WEATHER PROOF PLUG & SOCKETS

From IP 44 - 65 Total Solution Against Water & Power Protection

Authorised Certificates
















Authorised Certificates













Electrical Datas



WEIGHT OF COPPER FLATS IN KILOGRAMS PER METER

Size W T	Wt. in Kg/Mtr.	Current Capacity Amps	Size W T	Wt. in Kg/Mtr.	Current Capacity Amps
1/2"x 1/8"	0.360	62	11/2" x 1/8"	1.080	180
1/2"x 1/4"	0.720	125	11/2" x 1/4"	2.160	375
3/4" x 1/8"	0.540	90	2" x 1/4"	2.880	500
3/4" x 1/8"	1.080	180	2" x ½"	5.760	1000
1" x 1/16"	0.360	62	21/2" x 1/4"	3.600	625
1" x 1/8"	0.720	125	21/2" x ½"	7.200	1250
1" x 1/4"	1.440	250	3" x 1/4"	4.320	750
1" x ½"	2.880	500	3" x ½"	8.640	1500
11/4" x 1/8"	0.900	155	4" x 1/4"	5.760	1000
11/4" x 1/4"	1.800	310	4" x 1/2"	11.520	2000

WEIGHT OF CORRER WIRE

					R	

WEIG	FLAX	(IBLE C	ARLE			
Imperial Standard wire	Diameter	Sectional Area	Weight	Size	Mm2	Amps
Gauge (S.W.G.)	MM	Sq.mm	Kilos100m	3,0,0,0,1	2001	
7/0	12.70	126.6	113.1	16/.20	0.50	4
6/0	11.78	109.1	97.6	041.00	0.75	7
5/0	10.97	94.5	85.0	24/.20	0.75	1
4/0 3/0	10.16	81.0	72.6	32/.20	1.00	11
2/0	9.45 8.84	70.1 61.4	62.5 54.8	48/.20	1.50	14
0	8.23	53.1	47.7	1450004000		12,020
1	7.62	45.6	40.8	80/.20	2.50	19
2	7.01	38.6	34.7	128/.20	4.00	26
3	6.40	32.2	28.8	W 52		7.5
3	5.89	27.3	24.4	84/.20	6.00	33
5	5.38 4.87	22.7 18.7	20.4 16.6	140/.30	10.00	45
2 3 4 5 6 7	4.46	15.7	14.0	101/0.45	16.00	60
8 9	4.07 3.66	12.9 10.5	11.6 9.4	157/0.45	25.00	75
10	3.25	8.3 8.84	7.5	220/.0.45	35.00	95
11 12	2.95 2.64	5.48	6.11 4.92	314/0.45	50.00	125
13	2.34	5.48	4.92			2000
14	2.03	3.22	2.96	354/0.50	70.00	170
15 16	1.83 1.62	3.64 2.06	2.30 1.85	484/0.50	95	210
17	1.42	1.61	1.42	614/0.50	120	235
18 19	1.22 1.01	1.16 0.839	1.04 0.726	750/0.50	150	295
20 21	0.914 0.812	0.645 0.518	0.589 0.465	925/0.50	185	330
22	0.716	0.387	0.354	1221/0.50	240	400
23 24	0.609 0.558	0.258 0.239	0.261 0.221	1521/0.50	300	475
25	0.508	0.239	0.221	- Webs		
26	0.457	0.161	0.146	2036/0.50	400	500

BUSBAR SIZES

Switch Board	Busbar Size (Aluminium) mm				
Rating Amps	Phase	Nutral			
100	25 x 6	25 x 6			
200	38 x 6 63 x 6	38 x 6 38 x 6			
300	2 x 38 x 6	38 x 6			
400	2 x 50 x 6	50 x 6			
500	2 x 63 x 6 2 x 50 x 9	63 x 6 50 x 9			
600	2 x 75 x 6	75 x 6			
800	2 x 75 x 9 3 x 50 x 9	75 x 9 2 x 50 x 6			
1000	125 x 12	100 x 9			
1250	2 x 75 x 12 2 x 100 x 9	1 x 75 x 12 1 x 100 x 9			
1600	3 x 75 x 12	2 x 75 x 9			
2000	2 x 100 x 12	1 x 100 x 12			
2500	2 x 125 x 12 3 x 100 x 12	1 x 125 x 12 2 x 125 x 12			
3200	3 x 100 x 12	2 x 100 x 9			
400	2 x 152 x 12 4 x 125 x 12	1 x 152 x 12 2 x 125 x 12			

CURRENT RATINGS

FOR ALUMINIUM CONDUCTOR CABLES SUBJECT TO VOLTAGE DROP

Vulcanished Rubber P.V.C. or Polythene Insulated cables* sheathed with tough Rubber, P.V.C. lead

TWIN, 3-CORE AND 4-CORE

CONDITIONS OF INSULATION: One cable in run in conduit,

throughing or caring or in free

air or open trench

Ambient tempeature: 30 C (86F)

Size of conductor			twin-core o r single-pha		one 3-core or 4-core cable balanced three phase		
Nominal Area	Number and diameter or wire	d a med		te length of -volt drop a.c. meters	Currant rating	Approximate length of run for 1-volt drop	
mm2	mm	amp	d.c. meters	a.c. meters	amp	meters	
1.5 2.5 4 6 10 16 25 35 50*	1/1.40 1/1.80 1/2.24 1/2.80 1/3.55 7/1.70 7/2.24 7/2.50 7/3.00 19/1.80	10 15 20 27 34 43 59 69	2.3 2.5 2.9 3.4 4.2 5.3 6.6 7.1 7.7	2.3 2.5 2.9 3.4 4.2 5.3 6.6 7.1 7.7	7 11 14 19 24 30 42 48 62	3.7 3.9 4.8 5.5 6.8 8.7 10.8 11.7	
70 95 120 150 185 225 240 300	19/2.24 19/2.50 37/2.06 37/2.24 37/2.50 37/2.80 37/3.00 61/2.50	118 135 162 181 209 240 263 2989	9.0 9.8 10.8 11.4 12.3 13.5 14.0 14.6	8.8 9.5 10.3 10.7 11.2 11.7 11.9 12.1	82 94 114 127 146 169 185 202	14.7 15.7 16.8 17.5 18.4 19.1 19.5 20.0	

*These ratings apply for P.V.C. Insulated and Polythene insulated cables the maximum conductor size of wich is 50 mm2 At rated current

Ambient temperature for ambient temperature other than 30 C (86F) multiply the current rating and divide the lengths for 1-volt drop by the appropriate factor below :

Ambient air temperature	25C (77F)	35C (95F)	40C (104F)	45C (113F)
Rating factor	1.13	0.86	0.6	0.47
Grouping Factor	11000	0.00		
Number of cables	2	3	4	5
Rating factor	0.8	0.7	0.65	0.6

POWER CAPACITOR FOR DIRECT CONNECTION INDUCTION MOTORS CAPACTORS KVAr AT MOTOR SPEED OF

Meter HP	3000 rpm	1500 rpm	1000 rpm	750 rpm	600 rpm	500 rpm
5 7.5 10 15 20 20 30 40 50 75 100 125 150 250	223356790125050045	2 2 3 4 6 7 8 10 11 14 16 22 32 450	234578921550505555 1150505555 455	3357899105788910578891058910589105891058910589105891058910	335789060552554555	3357 102150225 3350 450 670

A GENERAL IDEA ABOUT THE POWER CONSUMPTION OF HOME APPLIANCES

Table Fan 40W Ceiling Fan 60W

Electric Iron

Imersion Heater Coil Stove Refrigerator

60W 400W to 750W 250W to 1000W 1250W to 2000W 90W (165 Ltr. Fridge consume 1 Unit per day average) 4 to 7 W Refrigerator 200W to 350W (without heater) 1500W to 200W (with heater) 350W to 500W 1500 to 3000W 500 VA stabilizer for Washing Machine Washing Machine Grinder / Mixie

1500 to 3000W 20 to 40W 1500 to 2000W 60 to 90W Window Type A/c Stabilizer for Air conditioner Water Heater Television Sets

Out of above items like auto elecric Iron, auto coil Stove, Water Heater, Refrigerator, Air Conditioners having Thermostat controls consumptions is only according to its usage.



INDUSTRY LEADER IN DESIGN & PERFORMANCE - WIRES & CABLES



IS: 694: 1990
IS: 1554 Part-1: 1988
IS: 7098 Part-1: 1988
CM/L-3060134
CM/L-3060033



CABLES



UG CABLES







GANDHI INDUSTRIAL ELECTRICALS

@ 139, Linghi Chetty Street, Chennai - 600 001.

S Phone: +91-44-25262521, 42167609, 42625670.

● Mobile: 98400 93444, 98400 39444, 98400 47775

E-mail: gandhibrothers1998@gmail.com

E-mail : gandhibrothers@rediffmail.com

Web : www.gandhielectrical.com